

THREADED TEE


Plasson's Threaded Tees are made from high quality polypropylene, offering both durability and reliability. Watermark approved and suitable for potable water (AS/NZS 4020), they meet AS/NZS 4129 standards. Their hexagon shape ensures easy handling, while male tapered threads maximize sealing. UV, chemical, and corrosion-resistant, this item is lightweight, durable, and easy to work with.

FEATURES AND BENEFITS

- Heavy duty Polypropylene material
- Suitable for potable water (AS/NZS 4020), Watermark approved
- ISO 7.1 BSP thread conforms to AS/NZS 4129:2020
- UV, chemical and corrosion resistant
- Light and durable - easy to work with

90° Threaded Tee


5050



Product Code	Size Rp	H	l2	Bag	Carton	W	PN
5040001	1/2"	64	18	10	700	28	16
5040002	3/4"	68	19	10	500	39	16
5040003	1"	81	21	10	260	61	16
5040006	1 1/4"	96	25	5	140	114	10
5040004	1 1/2"	108	25	5	90	157	10
5040005	2"	130	30	5	60	205	10

90° Threaded Tee with S/S Reinforcing Ring

5041



Product Code	Size Rp	H	l2	Bag	Carton	W	PN
5041001	1.1/4"	96	25	5	150	140	16
5041002	1.1/2"	108	25	5	204	90	16
5041003	2"	30	30	5	226	60	16

TECHNICAL SPECIFICATIONS

- Body: Polypropylene, high-grade copolymer.
- Reinforcing Ring: Stainless steel I.

INSTALLATION

Before installation ensure that the end of the pipe to be inserted into the fitting is free of scratches and other imperfections and that both the pipe and the fitting itself are clean of sand, mud, stones etc. Do not over tighten nut when closing. Never use wrenches or spanners with handle lengths longer than 46 cm - excessive torque during tightening can spread nut cone and result in pull outs. If fittings are reused, Plasson recommend replacing the grip ring with a new one. Refer to individual installation instructions.

THREADS

- All threads conform to ISO-7/1 (BSPT), BS 21 - 1973, DIN 2999, NEN 3258, AS 1722 Part 1 - 1975.
- All internal (female) threads smaller are parallel (Rp).
- Plasson recommend the use of PTFE tape in threaded

CHEMICAL RESISTANCE

PLASSON threaded fittings are made from high quality polypropylene resins.

OPERATING TEMPERATURES

Refer to the PIPA POP013 guidelines.

Link: <https://pipa.com.au/technical/pop-guidelines/>

QUALITY CERTIFICATES

Plasson fittings are tested and approved according to AS/NZ 4129.