


PLASSADDLE - ACME Threaded Outlet

The PLASSADDLE is a modern innovation, it is a mechanical tapping saddle with not bolts! Developed for metric poly pipe, the Plassaddle offers superior sealing, anti rotation capabilities and fast installation. Fully rated to PN16, these ACME outlet saddles are common in modern sports turf irrigation systems for lateral to sprinkler riser assemblies.



FEATURES AND BENEFITS

- Heavy Duty Polypropylene material
- 50 year design life
- Rated to PN16 for water - High pressure applications
- Suitable for potable water (AS/NZS 4020)
- Bolt free installation



Product Code	Size d x ACME	B	L	E1	H1	H2	Bag	Carton	W	PN
1630051	63 x 1"	91	89	102	136	49	5	50	387	16
1630052	63 x 1.1/4"	91	89	102	146	58	5	50	390	16
1630053	63 x 1.1/2"	91	89	102	136	49	5	50	373	16
1630054	75 x 1"	99	90	102	148	49	1	50	425	16
1630055	75 x 1.1/4"	99	90	102	157	58	1	50	426	16
1630056	75 x 1.1/2"	99	90	102	148	49	1	50	409	16
1630057	90 x 1"	119	94	102	163	49	1	50	464	16
1630058	90 x 1.1/4"	119	94	102	173	58	1	50	462	16
1630059	90 x 1.1/2"	119	94	102	163	49	1	50	446	16
1630060	110 x 1"	141	97	102	180	49	1	40	505	16
1630061	110 x 1.1/4"	141	97	102	190	58	1	40	502	16
1630062	110 x 1.1/2"	119	97	102	180	49	1	40	488	16
1630063	125 x 1"	157	100	102	198	49	1	36	570	16
1630064	125 x 1.1/4"	157	100	102	207	58	1	36	567	16
1630065	125 x 1.1/2"	157	100	102	198	49	1	36	553	16
1630066	160x1"	197	106	102	235	49	1	28	765	16
1630067	160 x 1.1/4"	197	106	102	235	58	1	28	713	16
1630068	160 x 1.1/2"	197	106	102	235	49	1	28	690	16
1630069	180x1"	220	110	102	255	49	1	24	817	16
1630070	180 x 1.1/4"	220	110	102	264	58	1	24	833	16
1630071	180 x 1.1/2"	220	110	102	255	49	1	24	802	16

TECHNICAL SPECIFICATIONS

- Clamp arms: Glass Reinforced Polypropylene.
- Nut: Glass Reinforced Polyamide.
- Pressurised Body: Polypropylene PPB.
- Seal: EPDM.

INSTALLATION

Before installation ensure that the pipe is free of scratches and other imperfections and that both the pipe and the fitting itself are clean of sand, mud, stones etc. Assembly is recommended with Plasson Alloy Wrench 40-75 P/N 7990007.

THREADS

- ACME for o-ring sealing.
- BSP threaded outlets available.

OPERATING TEMPERATURES

Refer to the PIPA POP013 guidelines.

Link: <https://pipa.com.au/technical/pop-guidelines/>

QUALITY CERTIFICATES

Plasson BSP outlet Plassaddle range is third party certified to conform to AS/NZS4129:2020. This certification is backed up with Watermark approval and WSAA Appraisals.