


METRIC COUPLINGS

The Plasson Metric Compression Wall Plated Elbow is made using heavy-duty polypropylene and a unique Captive O-Ring for a watertight seal. Rated to PN16 for water, it's ideal for potable and recycled water, compressed air, and other industrial applications. Watermark-approved, this fitting is compact, UV, chemical, and corrosion-resistant, it is suitable for tight spaces, and is available with optional enhanced O-rings.



Product Code	Size d x Rp	E	I	I2	A	A1	A2	H	Bag	Carton	W	PN
7750001	16 x 1/2"	39	50	18	76	40	38	110	1	150	98	16
7750002	20 x 1/2"	48	57	18	78	40	38	110	1	150	92	16
7750003	25 x 3/4"	54	58	19	81	40	38	120	1	100	115	16

TECHNICAL SPECIFICATIONS

- Body: Polypropylene, high-grade copolymer.
- Nut: Polypropylene, high-grade copolymer.
- Grip Ring: Acetal POM (CPVC also available).
- Seal: NBR or EPDM (FPM also available).
- Reinforcing Ring: Stainless steel on all female offtakes from 1" up to 4".
- Bolts (160mm fittings): Plated steel.
- Nuts (160mm fittings): Stainless steel.

INSTALLATION

Before installation ensure that the end of the pipe to be inserted into the fitting is free of scratches and other imperfections and that both the pipe and the fitting itself are clean of sand, mud, stones etc. Do not over tighten nut when closing. Never use wrenches or spanners with handle lengths longer than 46 cm - excessive torque during tightening can spread nut cone and result in pull outs. If fittings are reused, Plasson recommend replacing the grip ring with a new one. Refer to individual installation instructions.

FEATURES AND BENEFITS

- Heavy Duty Polypropylene material
- Unique Captive O-Ring creates a watertight connection
- Rated to PN16 for water - High pressure applications
- Suitable for potable water (AS/NZS 4020), Watermark approved AS/NZS 4129:2020
- Suitable for water, recycled water, compressed air, and other industrial applications
- UV, chemical and corrosion resistant
- Impact and abrasion resistant
- Compact design for tight spaces
- O-rings and grip rings with higher chemical resistance available

THREADS

- All threads conform to ISO-7/1 (BSPT),
- BS 21 - 1973, DIN 2999, NEN 3258, AS 1722 Part 1 - 1975.
- All internal (female) threads smaller than 3" are parallel (Rp).
- All other threads (male and female) are tapered (R).
- Plasson recommend the use of PTFE tape in threaded

CHEMICAL RESISTANCE

PLASSON Fittings are supplied, as standard, with polyacetal split rings and NBR O-rings which are suitable for water. For aggressive chemical applications CPVC split rings and EPDM or FPM O-rings can be supplied to produce a higher chemical resistance.

OPERATING TEMPERATURES

Refer to the PIPA POP013 guidelines.
 Link: <https://shorturl.at/jDKWZ>

QUALITY CERTIFICATES

Plasson fittings are tested and approved according to ISO 17885 (replaced ISO 14236), water and AS/NZ 4129.