


90° THREADED TEE WITH SS REINFORCING RING

5041

Plasson threaded fittings are manufactured from heavy-duty Polypropylene for increased strength and enhanced chemical resistance. The 90 degree Threaded Tee provides a three-way BSP connection with parallel female threads (Rp). This variant features a stainless steel reinforcing ring. Threads are made to ISO 7.1, equivalent to Australian Standard AS ISO 7.1. The enhanced stiffness of the Plasson Polypropylene fitting ensures a good seal between male and female threads. WaterMark approved and suitable for potable water (AS/NZS 4020), the fitting is UV, chemical and corrosion resistant — lightweight, durable and easy to work with.

FEATURES AND BENEFITS

- Heavy duty Polypropylene material
- Enhanced chemical resistance
- Rated to PN16 for water
- Parallel female threads (Rp) to ISO 7.1
- Hexagonal body for easy use with all standard tools
- Stainless steel reinforcing ring
- UV, chemical and corrosion resistant
- Suitable for potable water (AS/NZS 4020), WaterMark approved
- Certified to AS/NZS 4129:2020 – ISO Type 5 and WaterMark licences



Product Code	Size Rp	H	l2	Bag	Carton	W	PN
5041001	1¼"	96	25	5	140	150	16
5041002	1½"	108	25	5	90	204	16
5041003	2"	130	30	5	60	226	16

Dimensions in mm. W = weight (g). PN = pressure rating for water at 20°C.

TECHNICAL SPECIFICATIONS

- Body: Polypropylene (PP), high-grade copolymer.
- Reinforcing ring: stainless steel.
- Threads to ISO 7.1 / AS ISO 7.1.

INSTALLATION

A jointing medium – typically PTFE thread tape – is required to form a seal in BSP threaded connections. Ensure threads are clean and free of debris before assembly. Refer to individual installation instructions supplied with each fitting.

THREADS

- Female threads are parallel (BSPP), referred to as Rp.
- Plasson recommend the use of PTFE tape in BSP threaded connections.

OPERATING TEMPERATURES

Refer to the PIPA POP013 guidelines.

Link: <https://pipa.com.au/technical/pop-guidelines/>

QUALITY CERTIFICATES

Plasson threaded fittings are certified to AS/NZS 4129:2020 and hold both ISO Type 5 and WaterMark licences. Suitable for potable water in accordance with AS/NZS 4020.